

Power

Pathfinder® 10kW

Modular Switched Mode Rectifier



- Available in 208 Amps @ 48VDC
- 10kW per 3 RU module
- Unique power limiting feature
- Wide range 3-phase AC input
- Optimized for the SM series of controllers
- High efficiency with power factor correction
- Hot swappable rectifier
- Front panel LCD standard

Argus' complete and innovative family of communications-grade rectifiers offers more power at the lowest cost. Years of research and customer consultation have enabled Argus to develop an exceptionally cost effective rectifier that meets the complex demands of today's advanced digital communications equipment.

Pathfinder's hot swappable, front-access design incorporates an advanced switching technology for higher performance and greater reliability. The SM series of system controller provides rectifier setup, adjustment and control in a single-step process. Wide range AC input provides protection from power line disturbances and eliminates nuisance alarms.

SPECIFICATIONS

Rectifier Module(s)		FEATURES CONT'D		Environmental	
ELECTRICAL	Input voltage:	187 to 264 VAC three phase, three wire Delta connected 324 to 458 VAC three phase, four wire Wye connected 324 to 509 VAC three phase, four wire Wye connected	Adjustments:	Float voltage Equalize voltage High voltage alarm Low voltage alarm High voltage shutdown Current limit Slope Start delay	Temperature Standard: 0° to 60°C (32° to 140°F) Extended: -40° to 60°C (-40° to 140°F) Storage: -40° to 70°C (-40° to 158°F)
	Input frequency:	47 to 63Hz	Protection:	Current limit/short circuit Start delay Input/output fuses Output high voltage shutdown Power limiting Thermal foldback/shutdown Input transient AC low line foldback/shutdown AC high voltage shutdown	Humidity: 0 to 95% R.H. non-condensing
	Power:	10kW continuous/module			Elevation: -500 to 2800m (-1640 to 9186 ft)
	Power factor:	>0.99 true (50-100% load) (208 to 277 and 360 to 480 VAC)			
	Efficiency:	90% at 75 to 100% load (nominal Vin)			
	Output voltage:	42 to 60 VDC			
	Output current:	185A @ 54 VDC (235A maximum)			
	Regulation:	-0.2% ±25mV, line and load at 0.2% slope (static)			
	Transient response:	<1% deviation and 2msec to 0.1% of output for 50 to 100% load step <2% deviation for 10 to 90% load step			
	Noise Voice band: Wide band:	<22 dBrnC with batteries <10mV RMS (10kHz to 10MHz) <150mV pk to pk (10kHz to 100MHz) See Standards <60dBa at 1m (3 ft)			
MECHANICAL	EMI: Acoustic:				
	TIF (Current):	<120 at 100% load			
	Dimensions mm: inches:	246 H x 130 W x 305 D 9.7 H x 5.1 W x 12.0 D			
	Weight:	31.3 kg (69 lb.)			
	FEATURES				
	Indicators:	AC mains OK - green LED Module OK - green LED Module fail - red LED 2x16 character LCD			
	Shelf alarms:	Module fail alarm contacts			
	Controls:	Power on/off button Remote equalize Remote shutdown RS-485 interface Arrow keys (adjust/scroll) Enter/select key			
		Shelves		Standards	
		MECHANICAL		The Pathfinder 10kW is designed to meet the following:	
		Dimensions: mm: inches:	133 H x 533 W x 511 D 5.25 H x 21.0 W x 20.1 D	CSA: 22.2 N° 950-95 (to NRTL/C)	
		Weight:	7.8 kg (17.2 lb.)	UL: 1950-95 (under NRTL)	
		Mounting:	23" flush/offset/center mounting for single module	CE: EN60950-2nd Amend. 1-4	
		<i>Customer to provide rear support for flush mounting.</i>		FCC: Part 15, Class A	
		CONNECTIONS		ANSI/IEEE: C62.41 Category B3	
		Input:	Box type terminal block 6 to 16mm² (#10 to 6 AWG)	Bellcore: GR-63-CORE 4.3.1 and 4.4.4	
		Output:	3/8" threaded inserts on 1" centers	EMC Emissions: EN55022 (CISPR 22) Class A EN61000-3-2	
		Chassis ground:	Compression lug 6 to 16mm² (#10 to 6 AWG)	Immunity: EN 61000-4-2 to -6 EN 61000-4-11 ENV 50204	
		Alarms/control:	Terminal block 0.55 to 1.5mm² (#20 to 16 AWG)		
		SM communication:	RJ 12 offset		

For more information and detailed drawings, visit argusdcpower.com

Canada
United States

Argus Technologies Ltd. Vancouver, BC, Canada Tel: (604) 436-5900 Fax: (604) 436-1233
Argus Technologies Inc. Bellingham, WA, U.S.A. Tel: (360) 671-7054 Fax: (360) 671-7096

Argus Technologies

Copyright © 2003 Argus Technologies. All rights reserved. Argus® and Pathfinder® are registered trademarks of Argus Technologies. Printed in Canada #048-548-10 (2003/03).

Please note: Argus reserves the right to make changes to the products and information contained in this document without notice. Please contact your sales representative for the most up-to-date product specifications.